


If there are any questions regarding this Preliminary Amendment or this application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

It is respectfully requested that, if necessary to effect a timely response, this paper be considered as a Petition for an Extension of Time sufficient to effect a timely response and shortages in other fees, be charged, or any overpayment in fees be credited, to the Account of Evenson, McKeown, Edwards & Lenahan, P.L.L.C., Deposit Account No. 05-1323 (Docket #420/50943).

April 4, 2002

Respectfully submitted,



Vincent J. Sunderdick  
Registration No. 29,004

CROWELL & MORING, LLP  
P.O. Box 14300  
Washington, DC 20044-4300  
Telephone No.: (202) 624-2500  
Facsimile No.: (202) 628-8844

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

1. [Sound] A sound pressure level calibrator for calibrating a sound pressure level sensor, comprising:  
  
a pistonphone [(1)] for producing a sound pressure;  
  
and a high-pressure adapter [(2)], which is connected to an output of the pistonphone [(1)], wherein the [characterized in that]  
  
the high-pressure adapter [(2)] [is embodied as] includes a  $\lambda/4$  resonator to amplify the produced sound pressure and [has] an expanded adapter opening [(7)] with a sealing ring [(8)] for a soundproof connection to a said sound pressure level sensor [that is] to be calibrated.
  
2. [Sound] The sound pressure level calibrator as claimed in Claim 1, [characterized in that] wherein the resonator [(6)] is embodied as] is a tube of a length (L) with a constant diameter (d).
  
3. [Sound] The sound pressure level calibrator as claimed in claim 1, wherein [one of claims 1 or 2, characterized in that, to improve the soundproof connection of] the high pressure adapter [(2) to the sound pressure level sensor a], further includes an integral mechanical compensation link [(9)] is integrated in the high pressure adapter (2) and a sealing ring is inserted into the adapter opening (7)] in order to improve the soundproof connection of the high pressure adapter to the sound pressure level sensor.

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
0	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100

- [illegible]